

Műszaki adatok



Eaton 111683

Eaton xEffect CS LV systems Switch- & Controlgear Enclosure. Wall enclosure with mounting plate, HxWxD=400x400x150mm

Általános jellemzők

PRODUCT NAME	Eaton xEffect CS enclosure single door
CATALOG NUMBER	111683
EAN	4015081112425
PRODUCT LENGTH/DEPTH	150 mm
PRODUCT HEIGHT	400 mm
PRODUCT WIDTH	400 mm
PRODUCT WEIGHT	8.72 kg

COMPLIANCES

UL CSA09 (may be provided with metal sub-panel, no back mounted components are allowed between sub-panel and the back sheet metal enclosure)
RoHS conform
UL 508A; CSA-C22.2 No.14;
IEC/EN 62208; CE marking

CERTIFICATIONS

UL (Category Control Number NITW)
In accordance with Directive 2015/863/EU of the European Parliament and Council
UL (File No. E336299)
IEC/EN 62208
UL CSA08 (request filed)

CATALOG NOTES

Foamed polyurethane sealing throughout.
Impact resistance category IK10 to EN 62262. Sheet steel mounting plate.
Bottom plate with foamed gasket. Single door, door stop on the right, door opening angle 120°. Door hinge pins with quick chang

MODEL CODE	CS-44/150
-------------------	-----------



Powering Business Worldwide

Kiegészítő információk

FEATURES	Pole fastening Wall build in
FITTED WITH:	Including M6 threaded welded studs for earth conductor connections in the door: Mounting plate Cover Door
FUNCTIONS	Floor standing enclosure
RAL-NUMBER	7035

SPECIAL FEATURES

- Enclosed, foamed gasket
- Foamed polyurethane sealing throughout.
- Impact resistance category IK10 to EN 62262.
- Sheet steel mounting plate
- Bottom plate with foamed gasket.
- Single door, door stop on the right, door opening angle 120°
- Door hinge pins with quick change technology.
- Standardized locking system with sash fastener.
- Powder coating RAL 7035 inside and outside
- Lock, 3 mm double ward key
- Including M6 threaded welded studs for earth conductor connections in the door
- Side plates without apertures
- Top plate without apertures

SUITABLE FOR	Metrical mounting
USED WITH	Industrial control panels

Fő jellemzők

COLOR	Gray Light gray (RAL 7035)
TYPE	• Wall-mounting housing CS • Wall-mounting housing with mounting plate

Konstrukció igazolás az IEC/EN 61439 szerint

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
-------------------------------	--

10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility.
-----------------------------------	--

10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility.
--	--

10.13 MECHANICAL FUNCTION	Meets the product standard's requirements.
----------------------------------	--

10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
------------------------------------	--

10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
---	--

10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
---	--

10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
---	--

10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
---	--

10.2.5 LIFTING	Does not apply to enclosures without lifting aids.
-----------------------	--

10.2.6 MECHANICAL IMPACT	IK10
---------------------------------	------

10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
----------------------------	--

10.3 DEGREE OF PROTECTION OF ASSEMBLIES	IP66
--	------

10.4 CLEARANCES AND CREEPAGE DISTANCES	Is the panel builder's responsibility.
---	--

10.5 PROTECTION AGAINST ELECTRIC SHOCK	< 0.1 Ω; meets the product standard's requirements.
---	---

10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Is the panel builder's responsibility.
---	--

10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
--	--

Konstrukció igazolás az IEC/EN 61439 szerint

AMBIENT OPERATING TEMPERATURE DETAILS	-25 °C - 40 °C
--	----------------

10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	$U_i = 1000 \text{ V AC}$
10.9.3 IMPULSE WITHSTAND VOLTAGE	Does not apply to basic enclosures as defined in EN 62208.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Does not apply to metal enclosures.

Technical data - mechanical

CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78; Damp heat, cyclical, to IEC 60068-2-30
COVER/DOOR ANGLE	120° door opening angle
COVER/DOOR PROFILE	2 door profiles
COVER/DOOR TYPE	Standard closure 3 mm double-ward key (door interlock) Door hinges on the right, can be converted by user Door hinges right Can be converted by user
DESIGN TYPE	Canted and seam welded, including two M6 threaded bolts for earth conductor connections inside the enclosure.
FLANGE PLATE DIMENSIONS	112 mm x 332 mm
INSTALLATION SITE	Indoor installation
INSTALLATION TYPE	Floor standing wall model
LOAD CAPACITY (DOOR)	25 kg
LOAD CAPACITY (MOUNTING PLATE)	500 kg payload, when brackets fitted in all four enclosure corners (vertically or horizontally) and the weights are symmetrically distributed within the enclosure. 200 kg
MATERIAL	Steel Steel plate
MATERIAL QUALITY	Other
MATERIAL THICKNESS (BODY)	1.2 mm
MATERIAL THICKNESS (BOTTOM PLATE)	2 mm
MATERIAL THICKNESS (DOOR)	1.2 mm
MOUNTING METHOD	Wall fastening 9 mm drilling dimensions for wall mounting (Back plate) Intermediate mounting
MOUNTING PLATE HEIGHT	370 mm
MOUNTING PLATE MATERIAL	Sheet steel, hot-galvanized
MOUNTING PLATE	350 mm

Melegedésvizsgálat az IEC 60890 szabványnak megfelelően

**HEAT DISS. AMBIENT
35°C DELTA T: 20°C WALL
MOUNT MIDDLE ENCL.
TOP (IEC 60890)** 22 W

**HEAT DISS. AMBIENT
35°C DELTA T: 35°C WALL
MOUNT MIDDLE ENCL.
TOP (IEC 60890)** 50 W

**HEAT DISS. AMBIENT
35°C DELTA T: 20°C WALL
MOUNT INDIVID. ENCL.
TOP (IEC 60890)** 25 W

**HEAT DISS. AMBIENT
35°C DELTA T: 20°C WALL
MOUNT STARTING ENCL.
TOP (IEC 60890)** 24 W

**HEAT DISS. AMBIENT
35°C DELTA T: 35°C WALL
MOUNT INDIVID. ENCL.
TOP (IEC 60890)** 55 W

**HEAT DISS. AMBIENT
35°C DELTA T: 35°C WALL
MOUNT STARTING ENCL.
TOP (IEC 60890)** 53 W

**HEAT DISS. WALL MOUNT
INDIVIDUAL ENCL. TOP** 25 W

**HEAT DISS. WALL MOUNT
MIDDLE ENCL. TOP** 22 W

**HEAT DISS. WALL MOUNT
STARTING ENCL. TOP** 24 W

**THERMAL DISSIPATION
(DELTA T = 20 K)
ACCORDING TO IEC/TR
60890** 25 W

WIDTH	
NUMBER OF CONNECTOR HOLES	0
NUMBER OF COVERS/DOORS	1
NUMBER OF HINGES	2
NUMBER OF LOCKS	1
PERMISSIBLE LOAD OF THE DOOR(S) ACCORDING TO IEC 62208 - MAX	250 N
PERMISSIBLE LOAD OF THE ENCLOSURE ACCORDING TO IEC 62208 - MAX	2250 N
PERMISSIBLE LOAD OF THE MOUNTING PLATE ACCORDING TO IEC 62208 - MAX	2000 N
SURFACE FINISHING	Powder coating Semi-textured Structured powder spray polyester based paint finish Gloss
SURFACE TREATMENT	Structured powder spray polyester based paint finish
THICKNESS OF MOUNTING PLATE	2 mm
WEIGHT OF MOUNTED COMPONENTS - MAX	225 kg
DEGREE OF PROTECTION	IP66 IEC: IP66, indoor; UL/CSA Types 1, 12, indoor only. 12 (NEMA) IP23 (with ventilating plates) IK10 IK10 (impact resistance)

Erőforrások

BROSSÚRÁK	eaton-xeffect-cs-new-features-fl015002zu.pdf
MCAD MODEL	DA-CS-cs2520_150_111683 eaton-front-access-switchboard-mcad-drawings-cs2520-150.dwg
MEGFELELŐSÉGI NYILATKOZATOK	eaton-enclosure-declaration-of-conformity-eu250381en.pdf
TANÚSÍTVÁNYOK	eaton-xeffect-cs-enclosure-declaration-of-conformity-en-us.pdf
TELEPÍTÉSI ÚTMUTATÓ	IL2521

PROJEKT NEVE:

PROJEKT SZÁMA:

KÉSZÍTETTE:

DÁTUM:



Eaton Corporation plc Eaton House
30 Pembroke Road
DUBLIN, ÍRORSZÁG...
Eaton.com

© 2026 Eaton. Minden jog fenntartva.

Kövessen bennünket a közösségi médiában, hogy első kézből értesüljön a legújabb termékekről és információkról.

