

Műszaki adatok



Eaton 111717

Eaton xEffect CS LV systems Switch- & Controlgear Enclosure. Wall enclosure with mounting plate, HxWxD=1200x600x250mm

Általános jellemzők

PRODUCT NAME	Eaton xEffect CS enclosure single door
CATALOG NUMBER	111717
EAN	4015081112760
PRODUCT LENGTH/DEPTH	250 mm
PRODUCT HEIGHT	1200 mm
PRODUCT WIDTH	600 mm
PRODUCT WEIGHT	49.54 kg
COMPLIANCES	RoHS conform UL 508A; CSA-C22.2 No.14; IEC/EN 62208; CE marking UL CSA09 (may be provided with metal sub-panel, no back mounted components are allowed between sub-panel and the back sheet metal enclosure)
CERTIFICATIONS	UL (Category Control Number NITW) UL (File No. E336299) In accordance with Directive 2015/863/EU of the European Parliament and Council UL CSA08 (request filed) IEC/EN 62208
CATALOG NOTES	Foamed polyurethane sealing throughout. Impact resistance category IK10 to EN 62262. Sheet steel mounting plate. Bottom plate with foamed gasket. Single door, door stop on the right, door opening angle 120°. Door hinge pins with quick chang
MODEL CODE	CS-126/250



Powering Business Worldwide

Kiegészítő információk

FEATURES	Pole fastening Wall build in
FITTED WITH:	Mounting plate Including M6 threaded welded studs for earth conductor connections in the door: Cover Door
FUNCTIONS	Floor standing enclosure
RAL-NUMBER	7035

SPECIAL FEATURES

- Bottom plate enclosed, foamed gasket, can be unscrewed for F3A-... flanges or for assembly by user
- Foamed polyurethane sealing throughout.
- Impact resistance category IK10 to EN 62262.
- Sheet steel mounting plate
- Bottom plate with foamed gasket.
- Single door, door stop on the right, door opening angle 120°
- Door hinge pins with quick change technology.
- Standardized locking system with sash fastener.
- Powder coating RAL 7035 inside and outside
- Lock, 3 mm double ward key
- Including M6 threaded welded studs for earth conductor connections in the door
- Side plates without apertures
- Top plate without apertures

Fő jellemzők

COLOR	Light gray (RAL 7035) Gray
TYPE	• Wall-mounting housing CS • Wall-mounting housing with mounting plate

SUITABLE FOR

Metrical mounting

USED WITH

Industrial control panels

Konstrukció igazolás az IEC/EN 61439 szerint

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
-------------------------------	--

10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility.
-----------------------------------	--

10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility.
--	--

10.13 MECHANICAL FUNCTION	Meets the product standard's requirements.
----------------------------------	--

10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
------------------------------------	--

10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
---	--

10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
---	--

10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
---	--

10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
---	--

10.2.5 LIFTING	Does not apply to enclosures without lifting aids.
-----------------------	--

10.2.6 MECHANICAL IMPACT	IK10
---------------------------------	------

10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
----------------------------	--

10.3 DEGREE OF PROTECTION OF ASSEMBLIES	IP66
--	------

10.4 CLEARANCES AND CREEPAGE DISTANCES	Is the panel builder's responsibility.
---	--

10.5 PROTECTION AGAINST ELECTRIC SHOCK	< 0.1 Ω; meets the product standard's requirements.
---	---

10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Is the panel builder's responsibility.
---	--

10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
--	--

Konstrukció igazolás az IEC/EN 61439 szerint

AMBIENT OPERATING TEMPERATURE DETAILS	-25 °C - 40 °C
--	----------------

10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	$U_i = 1000 \text{ V AC}$
10.9.3 IMPULSE WITHSTAND VOLTAGE	Does not apply to basic enclosures as defined in EN 62208.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Does not apply to metal enclosures.

Technical data - mechanical

CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78; Damp heat, cyclical, to IEC 60068-2-30
COVER/DOOR ANGLE	120° door opening angle
COVER/DOOR PROFILE	2 door profiles
COVER/DOOR TYPE	Closed Door hinges on the right, can be converted by user Standard closure 3 mm double-ward key (door interlock)
DESIGN TYPE	Canted and seam welded, including two M6 threaded bolts for earth conductor connections inside the enclosure.
FLANGE PLATE DIMENSIONS	172 mm x 432 mm
INSTALLATION SITE	Indoor installation
INSTALLATION TYPE	Floor standing wall model
LOAD CAPACITY (DOOR)	40 kg
LOAD CAPACITY (MOUNTING PLATE)	350 kg 500 kg payload, when brackets fitted in all four enclosure corners (vertically or horizontally) and the weights are symmetrically distributed within the enclosure.
MATERIAL	Steel plate Steel
MATERIAL QUALITY	Other
MATERIAL THICKNESS (BODY)	1.5 mm
MATERIAL THICKNESS (BOTTOM PLATE)	2 mm
MATERIAL THICKNESS (DOOR)	2 mm
MOUNTING METHOD	9 mm drilling dimensions for wall mounting (Back plate) Wall fastening Intermediate mounting
MOUNTING PLATE HEIGHT	1170 mm
MOUNTING PLATE MATERIAL	Sheet steel, hot-galvanized
MOUNTING PLATE WIDTH	550 mm

Melegedésvizsgálat az IEC 60890 szabványnak megfelelően

**HEAT DISS. AMBIENT
35°C DELTA T: 20°C WALL
MOUNT MIDDLE ENCL.
TOP (IEC 60890)** 92 W

**HEAT DISS. AMBIENT
35°C DELTA T: 35°C WALL
MOUNT MIDDLE ENCL.
TOP (IEC 60890)** 135 W

**HEAT DISS. AMBIENT
35°C DELTA T: 20°C WALL
MOUNT INDIVID. ENCL.
TOP (IEC 60890)** 106 W

**HEAT DISS. AMBIENT
35°C DELTA T: 20°C WALL
MOUNT STARTING ENCL.
TOP (IEC 60890)** 99 W

**HEAT DISS. AMBIENT
35°C DELTA T: 35°C WALL
MOUNT INDIVID. ENCL.
TOP (IEC 60890)** 149 W

**HEAT DISS. AMBIENT
35°C DELTA T: 35°C WALL
MOUNT STARTING ENCL.
TOP (IEC 60890)** 142 W

**HEAT DISS. WALL MOUNT
INDIVIDUAL ENCL. TOP** 106 W

**HEAT DISS. WALL MOUNT
MIDDLE ENCL. TOP** 92 W

**HEAT DISS. WALL MOUNT
STARTING ENCL. TOP** 99 W

**THERMAL DISSIPATION
(DELTA T = 20 K)
ACCORDING TO IEC/TR
60890** 106 W

NUMBER OF CONNECTOR HOLES	0
NUMBER OF COVERS/DOORS	1
NUMBER OF F3A FLANGES	2
NUMBER OF HINGES	3
NUMBER OF LOCKS	1
PERMISSIBLE LOAD OF THE DOOR(S) ACCORDING TO IEC 62208 - MAX	400 N
PERMISSIBLE LOAD OF THE ENCLOSURE ACCORDING TO IEC 62208 - MAX	3900 N
PERMISSIBLE LOAD OF THE MOUNTING PLATE ACCORDING TO IEC 62208 - MAX	3500 N
SURFACE FINISHING	Gloss Structured powder spray polyester based paint finish Semi-textured Powder coating
SURFACE TREATMENT	Structured powder spray polyester based paint finish
THICKNESS OF MOUNTING PLATE	3 mm
WEIGHT OF MOUNTED COMPONENTS - MAX	390 kg
DEGREE OF PROTECTION	IP66 IP23 (with ventilating plates) IEC: IP66, indoor; UL/CSA Types 1, 12, indoor only. 12 (NEMA) IK10 IK10 (impact resistance)

Erőforrások

BROSSÚRÁK	eaton-xeffect-cs-new-features-fl015002zu.pdf
MCAD MODEL	DA-CS-cs108_300_111717 eaton-front-access-switchboard-mcad-drawings-cs108-300.dwg
MEGFELELŐSÉGI NYILATKOZATOK	eaton-enclosure-declaration-of-conformity-eu250381en.pdf
TANÚSÍTVÁNYOK	eaton-xeffect-cs-enclosure-declaration-of-conformity-en-us.pdf
TELEPÍTÉSI ÚTMUTATÓ	IL2521

PROJEKT NEVE:

PROJEKT SZÁMA:

KÉSZÍTETTE:

DÁTUM:



Eaton Corporation plc Eaton House
30 Pembroke Road
DUBLIN, ÍRORSZÁG...
Eaton.com

© 2026 Eaton. Minden jog fenntartva.

Kövessen bennünket a közösségi médiában, hogy első kézből értesüljön a legújabb termékekről és információkról.

