

# EC350C8

## FLUSH MOUNTING JUNCTION BOX WITH LID DIM. 392X152X70

Enclosures > Recessed > Recessed junction boxes > Series 350 - masonry > Flush mount junction boxes > Orange boxes

### Technical Symbols/Marks/Approvals

IP40 | HF | GWT 650° | CE | RoHS II | MADE IN ITALY

### Norms

EN 60670-1 EN 60670-22

## Description

Recessed junction box for masonry walls. Made of impact-resistant, halogen-free technopolymer. Complete with lid and fixing screws. Paintable embossed lid. Resistance to abnormal heat up to 650°C (GWT). Manufactured in accordance with EN 60670-1:2005, EN 60670-22:2006. Installation temperatures: minimum -15°C, maximum +60°C. IP40 protection rating.
Dimensions: 392x152x70 mm
Designed for 4 compartments



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

## Etim

### GROUP EG000048 - Connection material (electrotechnical)

### CLASS EC002601 - Box/housing for built-in mounting in the wall/ceiling

| | | | | | |
|---|---|---|---|---|---|
| **Max. conductor cross section** | 0 | **Mounting method** | Flush-mounted | **Degree of protection (IP)** | IP40 |
| **Material** | Plastic | **Halogen free** | Yes | **Surface protection** | Untreated |
| **Colour** | Orange | **Width** | 392 mm | **Model** | Other |
| **Length** | 152 mm | **Diameter** | 0 mm | **Cover model** | Blind cover |
| **Inner depth** | 69 mm | **Circuit integrity** | None | **Equipped with** | None |
| **Shape** | Rectangular | **Number of inlets** | 34 | **Inlet from the rear** | Yes |
| **Compliant with BS 4662** | No | **Couplable** | No | **Transparent cover** | No |
| **Pipe locking** | No | **Construction type** | Cable junction box | **Airtight** | No |
| **For tube diameter** | Other | **Cover attachment** | Screwed | **Sealable** | No |
| **With screening** | No | **Provided with revolving ring** | No | **Depth** | 0-69 mm |
| **For number of device inserts** | 0 | **Mounting switching equipment** | Screwing | **With screws** | Yes |
| **Housing feed-through by break-out opening** | Yes | **Housing feed-through by seal membrane** | No | **Housing feed-through by nozzle** | No |
| **Housing feed-through by step membrane** | No | **Pipe locking optional** | No | **Number of included spouts** | 0 |
| **Number of poles of the clamp** | 0 | **Clamp position fixed** | No | **Luminaire hook mounting** | No |
| **Nozzle** | None | **Special application** | None | **With partition panel** | No |

## Technical Characteristics

| | |
|---|---|
| **Preparation for compartments/DIN rails** | 4 / - |

## Documentation available for download



Certification

Serie 350
IMQ_CA02.01670_
2018.pdf



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

## Barcode

8032636760678
**Unit**
1 NR
0.185x0.075x0.425 [m]
0.525 [kg]

8057711599592
**Cardboard**
20 NR
0.405x0.605x0.55 [m]
10.5 [kg]



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.