elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET

EC410C4R

SMOOTH SIDED BOX IP56 DIM. 120X80X50



Envolvientes > Montaje en pared > Cajas de conexiones > 410 - paredes lisas > 410 - paredes lisas > Ip56 - libre de halÓgenos

Technical Symbols/Marks/Approvals

IP56 | GWT 650° | HF | IK08 | CE | RoHS II | MADE IN ITALY

Estándares

EN 60670-1 EN 60670-22

Etim

GROUP EG000048 - Connection material (electrotechnical)

CLASS EC002600 - Box/housing for surface mounting on the wall/ceiling

Rated insulation voltage Ui	400 V	**Mounting method**	Wall-/ceiling mounting	**Degree of protection (IP)**	IP56
Material	Plastic	**Halogen free**	Yes	**Surface protection**	Untreated
Colour	Grey	**Width**	120 etim.un.eu570448.abb	**Depth**	50 etim.un.eu570448.abb
Model	Junction box	**Length**	80 etim.un.eu570448.abb	**Diameter**	0 etim.un.eu570448.abb
Working temperature	-25-70 etim.un.eu570073.abb	**Explosion-tested version**	No	**For Ex-zone gas**	None
For Ex-zone dust	None	**Cover model**	Blind cover	**Circuit integrity**	None
Equipped with	None	**Shape**	Rectangular	**Number of inlets**	0
Inlet from the rear	No	**Transparent cover**	No	**Connectable**	No
For tube diameter	Other	**Mounting in the soil**	No	**Mounting under water**	No
Type of housing feed-through	None	**Cover attachment**	Screwed	**Castable**	Yes
Casting compound included	No	**Sealable**	No	**With screening**	No
Weatherproof	Yes				

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Documentation available for download



Certification

Serie 400 IP56
IMQ_EI884_2018.pdf

Barcode

8032636761385
Unit
1 NR
0.12 [kg]

8057711599837
Cardboard
100 NR
0.605x0.4x0.35 [m]
12 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.