

EC60054BE

WALL-MOUNT MOD. ENCL. IP40 400X600X130 54M WHITE (3x18) WHITE (T.B. 4x12)

Enclosures > Wall-mount > Wall modular enclosures > Series 600 - ip40 modular enclosures > Small distribution board > White - equipped

Technical Symbols/Marks/Approvals

IP40 | GWT 650° | RoHS II | MADE IN ITALY

Norms

EN 60670-1 EN 60670-24

Description

Wall-mounted consumer unit. Made of shockproof UV-resistant and halogen-free ABS-based technopolymer. Impact resistance rating IK08. Resistance to abnormal heat up to 650°C (GWT). Base and cover in halogen-free ABS-based technopolymer. Reversible cover. Smoked polycarbonate door. Self-adhesive circuit identification label included. Blanking plates for unused modules included. Fixing screw caps provided to maintain IP protection rating and double insulation. Mounted galvanized steel DIN rail. Adjustable to two heights. Manufactured in compliance with EN 60670-1:2005 and EN 60670-22:2013 standards. Installation temperatures: minimum –5°C, maximum +60°C. Operating temperatures: minimum -25°C, maximum +70°C. IP40 protection rating.
External dimensions 400x600x130 mm
54 DIN modules (3x18)
8 terminal blocks 6x10 mm - 12 holes
Power dissipation 72 W

Etim

GROUP EG000023 - Distribution boards

CLASS EC000214 - Small distribution board

Mounting method	Surface mounted	**Degree of protection (IP)**	IP40	**Width in number of modular spacings**	54
Colour	White	**Width**	400 mm	**Height**	600 mm
Depth	130 mm	**RAL-number**	9001	**UV resistant**	Yes
Type of covering	Door	**Type of door**	Single	**Transparent cover/door**	Yes
With lock	No	**Inner depth**	130 mm	**Number of rows**	3
Extension possible	No	**Housing material**	Plastic	**With mounting plate**	No
Signal passing door	No	**Type of closure**	Other	**Earthing terminal block**	Yes
Neutral terminal block	Yes	**DIN-rail**	Yes	**EMC-version**	No

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Technical Characteristics

dimensions	400x600x130 mm	**Mounting equipment**	2	**Terminal blocks/holes**	8x12
Power dissipation	72 W	**Tipo_Morsettiera**	2x16 + 10x10 mm²		

Documentation available for download



Instruction booklet

Istruzioni 600-610_0423.pdf



Certification

Serie 600-610 IMQ_CA02.00428_2018.pdf

Dimensions and technical drawings

EC60054_2025.pdf

Barcode

8053676572663

Unit

1 NR

5.39 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.