

R 25-40 230V

Modular contactor



ETI Code:	002462310
Depth:	60 mm
Rated operation current Ie at AC1:	25 A
IP rating:	IP40
Residual current type:	AC
Type description:	AC
Rated operational current Ie AC-1/AC-7:	25 A
Rated operational voltage (AC):	440 V
Rated control circuit voltage Uc (AC):	230 V
Current type:	AC
Rated Frequency:	50/60 Hz
No. of NO contacts:	4
Function:	Modular contactor
Type of Installation:	DIN rail
Catalogue Group:	R

[Online product page](#)

Documents



TECHNICAL DATA CATALOG



CE DECLARATION



2D FILE



3D FILE



EPLAN FILE

ETIM

Additional equipment possible	Yes
Voltage type (excitation voltage)	AC
Built-in depth	60 mm
Max. load fluorescent lamp	1,190 VA
Voltage type (operating voltage)	AC/DC
Degree of protection (IP)	IP20
Max. load fluorescent lamp (parallel compensated)	1,360 VA
Utilization category according to EN IEC 60947-4-1	AC-1
Max. load fluorescent lamp (Duo circuit)	2,552 VA
Number of contacts as normally open contact	4
Rated operation current	25 A
Max. incandescent lamp load	3,000 W
Width in number of modular spacings	2
Rated excitation voltage(Min)	230 V
Rated operating voltage(Min)	24 V
Rated operating voltage(Max)	440 V
Rated excitation voltage(Max)	230 V

Logistics

Product

EAN code for a single product	5904722903432
Net weight of the product	0.21 kg
Net width	35 mm
Net height	88 mm
Net depth	65 mm
Stock unit of measure	pcs

Basic Packaging

Basic packaging quantity	6 pcs
EAN code for a basic packaging	3838895141099
Basic packaging weight	1.26 kg
Basic Packaging Dimensions Height	216 mm
Basic Packaging Dimensions Width	90 mm
Basic Packaging Dimensions Depth	73 mm
Basic packaging volume	1.419 dm³

Transport Packaging

Transport packaging quantity	60 pcs
EAN code for a transport packaging	3838895161974
Transport packaging weight	12.85 kg
Transport Packaging Dimensions Height	190 mm
Transport Packaging Dimensions Width	225 mm
Transport Packaging Dimensions Depth	385 mm
Transport packaging volume	16.459 dm³
Pallet quantity	3,480 pcs
Customs tariff	85364900

Dimension

