

R 40-40 230V

Modular contactor



ETI Code:	002463410
Depth:	60 mm
Rated operation current I _e at AC1:	40 A
IP rating:	IP40
Residual current type:	AC
Type description:	AC
Rated operational current I _e AC-1/AC-7:	40 A
Rated operational voltage (AC):	440 V
Rated control circuit voltage U _c (AC):	230 V
Current type:	AC
Rated Frequency:	50/60 Hz
No. of NO contacts:	4
Function:	Modular contactor
Type of Installation:	DIN rail
Catalogue Group:	R

[Online product page](#)

Documents



TECHNICAL DATA CATALOG



CE DECLARATION



2D FILE



3D FILE



EPLAN FILE

ETIM

Additional equipment possible	Yes
Voltage type (excitation voltage)	AC
Built-in depth	60 mm
Max. load fluorescent lamp	2,975 VA
Voltage type (operating voltage)	AC/DC
Degree of protection (IP)	IP20
Max. load fluorescent lamp (parallel compensated)	2,805 VA
Utilization category according to EN IEC 60947-4-1	AC-1
Max. load fluorescent lamp (Duo circuit)	5,280 VA
Number of contacts as normally open contact	4
Rated operation current	40 A
Max. incandescent lamp load	6,000 W
Width in number of modular spacings	3
Rated excitation voltage(Min)	230 V
Rated operating voltage(Min)	24 V
Rated operating voltage(Max)	440 V
Rated excitation voltage(Max)	230 V

Logistics

Product

EAN code for a single product	5904722903531
Net weight of the product	0.36 kg
Net width	54 mm
Net height	88.8 mm
Net depth	65 mm
Stock unit of measure	pcs

Basic Packaging

Basic packaging quantity	4 pcs
EAN code for a basic packaging	3838895141198
Basic packaging weight	1.44 kg
Basic Packaging Dimensions Height	216 mm
Basic Packaging Dimensions Width	90 mm
Basic Packaging Dimensions Depth	73 mm
Basic packaging volume	1.419 dm³

Transport Packaging

Transport packaging quantity	40 pcs
EAN code for a transport packaging	3838895162131
Transport packaging weight	14.65 kg
Transport Packaging Dimensions Height	190 mm
Transport Packaging Dimensions Width	225 mm
Transport Packaging Dimensions Depth	385 mm
Transport packaging volume	16.459 dm³
Pallet quantity	2,160 pcs
Customs tariff	85364900

Dimension

R40,R63

Limits 190,120

