elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET

EC63004

FLUSH MOUNT.MOD.ENCLOSURE IP40 DIM. 154X160X80 4 MOD. GREY



Enclosures > Recessed > Recessed modular enclosures > Series 630 - masonry modular enclosures > Small distribution board > Grey -transparent door

Technical Symbols/Marks/Approvals

IP40 | GWT 650° | RoHS II | MADE IN ITALY

Norms

EN 60670-1 EN 60670-24

Description

Flush-mounting distribution board for masonry walls. Base made of high-impact technopolymer with low smoke emission. Resistance to abnormal heat up to 650°C (GWT). Halogen-free ABS technopolymer cover. Reversible cover. Smoked polycarbonate door. Option to install a cylinder safety lock. Door closure with spring-loaded sliding inserts. High-gloss finish on outer frame and door. Self-adhesive circuit identification labels included. Blanking covers for unused modules included. Galvanized steel DIN rail mounted on a removable and adjustable support for perfect horizontal alignment. Manufactured in compliance with EN 60670-1:2005 and EN 60670-22:2013 standards. Installation temperature range: minimum -15°C, maximum +60°C. IP40 protection degree.
External dimensions 154x160 mm
Base depth 80 mm
4 DIN modules
Dissipated power 9 W

Etim

GROUP EG000023 - Distribution boards

CLASS EC000214 - Small distribution board

Mounting method	Flush-mounted	**Degree of protection (IP)**	IP40	**Width in number of modular spacings**	4
Built-in depth	80 mm	**Colour**	Grey	**Width**	154 mm
Height	160 mm	**Depth**	97 mm	**Built-in height**	80 mm
RAL-number	7035	**Type of covering**	Door	**Type of door**	Single
Transparent cover/door	Yes	**With lock**	No	**Inner depth**	80 mm
Number of rows	1	**Extension possible**	No	**Housing material**	Plastic
With mounting plate	No	**Type of closure**	Other	**Earthing terminal block**	No
Neutral terminal block	No	**DIN-rail**	Yes	**EMC-version**	No

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Technical Characteristics

dimensions	154x160x80 mm	**Power dissipation**	9 W

Documentation available for download



Instruction booklet

Istruzioni 630-635_0125_0125.pdf



Certification

Serie 630 IMQ_CA02.01745_2020.pdf

Dimensions and technical drawings

EC63004_2025.pdf

Barcode

8032636763181

Unit

1 NR

0.165x0.175x0.105 [m]

0.5 [kg]

8059307210201

Cardboard

20 NR

0.605x0.4x0.35 [m]

10 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.