

EC63508BE

DRY LINING MODULAR ENCLOSURE 8 MOD. - TRANSPARENT DOOR - RAL9001 (1X8 T.B.)

Enclosures > Recessed > Recessed modular enclosures > Series 635 - dry lining modular enclosures > Small distribution board > White -transparent door - equipped

Technical Symbols/Marks/Approvals

IP40 | GWT 850° | RoHS II | MADE IN ITALY

Norms

EN 60670-1 EN 60670-24

Description

Flush-mounting distribution board for lightweight walls - plasterboard or wood. Base made of blue, high-impact technopolymer with low smoke emission. Resistance to abnormal heat up to 850°C (GWT). Halogen-free ABS technopolymer cover. Reversible cover. Smoked polycarbonate door. Option to install a cylinder safety lock. Door closure with spring-loaded sliding inserts. High-gloss finish on outer frame and door. Self-adhesive circuit identification labels included. Blanking covers for unused modules included. Galvanized steel DIN rail mounted on a removable and adjustable support for perfect horizontal alignment. Base fixing to the structure via brackets. Manufactured in compliance with EN 60670-1:2005 and EN 60670-22:2013 standards. Installation temperature range: minimum -15°C, maximum +60°C. IP40 protection degree.
External dimensions 240x194 mm
Base depth 80 mm
8 DIN modules
2 terminal blocks 6x10 mm - 8 holes
Dissipated power 18 W

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Etim

GROUP EG000023 - Distribution boards


CLASS EC000214 - Small distribution board

Mounting method	Flush-mounted/hollow wall	**Degree of protection (IP)**	IP40	**Width in number of modular spacings**	8
Built-in depth	80 mm	**Colour**	White	**Width**	240 mm
Height	194 mm	**Depth**	100 mm	**Built-in height**	80 mm
RAL-number	9001	**Type of covering**	Door	**Type of door**	Single
Transparent cover/door	Yes	**With lock**	No	**Inner depth**	80 mm
Number of rows	1	**Extension possible**	No	**Housing material**	Plastic
With mounting plate	No	**Type of closure**	Other	**Earthing terminal block**	Yes
Neutral terminal block	Yes	**DIN-rail**	Yes	**EMC-version**	No

Technical Characteristics

dimensions	240x194x80 mm	**Mounting equipment**	1	**Terminal blocks/holes**	2x8
Power dissipation	18 W	**Tipo_Morsettiera**	2x16 + 6x10 mm²		

Documentation available for download



Instruction booklet

Istruzioni 630-635_0125_0125.pdf

Dimensions and technical drawings

EC63508_2025.pdf

Barcode

8053676576920

Unit

1 NR

0.8611 [kg]

8059307214698

Cardboard

9 NR

7.7499 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.