

EC63572BE

DRY LINING MODULAR ENCLOSURE 72 MOD. - TRANSP. DOOR - RAL9001 (4X12 T.B.)

Enclosures > Recessed > Recessed modular enclosures > Series 635 - dry lining modular enclosures > Small distribution board > White -transparent door - equipped

Technical Symbols/Marks/Approvals

IP40 | GWT 850° | RoHS II | MADE IN ITALY

Norms

EN 60670-1 EN 60670-24

Description

Flush-mounting distribution board for lightweight walls - plasterboard or wood. Base made of blue, high-impact technopolymer with low smoke emission. Resistance to abnormal heat up to 850°C (GWT). Halogen-free ABS technopolymer cover. Reversible cover. Smoked polycarbonate door. Option to install a cylinder safety lock. Door closure with spring-loaded sliding inserts. High-gloss finish on outer frame and door. Self-adhesive circuit identification labels included. Blanking covers for unused modules included. Galvanized steel DIN rail mounted on a removable and adjustable support for perfect horizontal alignment. Adjustable to two heights. Base fixing to the structure via brackets. Manufactured in compliance with EN 60670-1:2005 and EN 60670-22:2013 standards. Installation temperature range: minimum -15°C, maximum +60°C. IP40 protection degree.
Equipped with asymmetrical 18-module windows that allow for varying the distance between DIN rails across three steps; DIN rails can be fixed in correspondence with the windows. DIN rails can be fixed at two heights. DIN module windows are replaceable with blank panels (item EC67018) to create mixed combinations and small automation systems. All windows are sealable.
External dimensions 450x853 mm
Adjustable window / DIN rail pitch 150-175-200 mm
Base depth 95 mm
72 DIN modules (4x18)
8 terminal blocks 6x10 mm - 12 holes
Dissipated power 90 W

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Etim

GROUP EG000023 - Distribution boards


CLASS EC000214 - Small distribution board

Mounting method	Flush-mounted/hollow wall	**Degree of protection (IP)**	IP40	**Width in number of modular spacings**	72
Built-in depth	95 mm	**Colour**	White	**Width**	450 mm
Height	853 mm	**Depth**	119 mm	**Built-in height**	95 mm
RAL-number	9001	**Type of door**	Double	**Transparent cover/door**	Yes
With lock	No	**Inner depth**	95 mm	**Number of rows**	4
Extension possible	No	**Housing material**	Plastic	**With mounting plate**	No
Type of closure	Other	**Earthing terminal block**	Yes	**Neutral terminal block**	Yes
DIN-rail	Yes	**EMC-version**	No		

Technical Characteristics

dimensions	450x853x95 mm	**Mounting equipment**	2	**Terminal blocks/holes**	8x12
Power dissipation	90 W	**Tipo_Morsettiera**	2x16 + 10x10 mm²		

Documentation available for download



Instruction booklet

Istruzioni 630-635_0125_0125.pdf

Dimensions and technical drawings

EC63572_COPERCHIO_2025.pdf

EC63572_FONDO_2025.pdf

Barcode

8054382041962

Unit

1 NR

6.89 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.