ECM24PT

Műanyag elosztó



ETI kód:	**001101012**
Sorok:	**2**
Katalóguscsoport:	**ECM süllyesztett, műanyag elosztószekrények, IP40**
Ajtó típusa:	**Átlátszó ajtó**
Méret:	**24**
Szerelési mód:	**Süllyesztett**
IP védettség:	**IP40**
Méret (Sorok száma):	**2**
Modulszám (Összes/soronként):	**24/12**
Ajtó (anyag, szín):	**Műanyag, Átlátszó**
Elosztó (anyag, szín):	**plastic, white**
PE/N sorkapcsok száma:	**13**
Lángállósság (°C):	**650 °C**
Névleges feszültség DC:	**400 V**
Névleges áram:	**63 A**
Névleges feszültség AC (V):	**400 V**

Online termékoldal

Dokumentumok

MŰSZAKI ADATKATALÓGUS

HASZNÁLATI ÚTMUTATÓ

NYILATKOZAT

2D FÁJL

3D FÁJL

EPLAN FÁJL

ETIM

Built-in depth	**68 mm**
Width	**283 mm**
DIN-rail	**Igen**
Type of covering	**Door**
Neutral terminal block	**Igen**
Transparent cover/door	**Igen**
Degree of protection (IP)	**IP40**
Mounting method	**Flush-mounted**
Signal passing door	**Igen**
Earthing terminal block	**Igen**
Built-in height	**336 mm**
Number of rows	**2**
Housing material	**Plastic**
Depth	**106 mm**
Built-in width	**273 mm**
Colour	**White**
Type of door	**Single**
Cover model	**Closed**
Height	**357 mm**
Width in number of modular spacings	**12**
RAL-number	**9 003**

Logisztika

Termék

Tömeg	**1,338 kg**
Net width	**283,6 mm**
Net height	**356,8 mm**
Net depth	**105,8 mm**
Stock unit of measure	**pcs**

Alapcsomagolás

Basic packaging quantity	**1 pcs**
EAN code for a basic packaging	**3838895456780**
Basic packaging weight	**1,338 kg**
Basic Packaging Dimensions Height	**283 mm**
Basic Packaging Dimensions Width	**357 mm**
Basic Packaging Dimensions Depth	**106 mm**
Basic packaging volume	**10,709 dm³**

Szállítási csomagolás

Transport packaging quantity	**5 pcs**
EAN code for a transport packaging	**3838895456797**
Transport packaging weight	**7,22 kg**
Transport Packaging Dimensions Height	**543 mm**
Transport Packaging Dimensions Width	**373 mm**
Transport Packaging Dimensions Depth	**298 mm**
Transport packaging volume	**60,357 dm³**
Pallet quantity	**140 pcs**
Customs tariff	**85381000**

Dimension

Flush mounted distribution board

type	Dimensions							Max. allowed power losses when Max. number of devices are installed	Static load
	A	B	C	D	E	F	G	Pde	
ECM4PT/ECM4PO	232 mm	139 mm	99 mm	-	123 mm	216 mm	69 mm	>10 W	520 g
ECM8PT/ECM8PO	232 mm	211 mm	99 mm	-	201 mm	212mm	68 mm	>16 W	1040 g
ECM12PT/ECM12PO	232 mm	283 mm	106 mm	-	273 mm	212 mm	68 mm	>25 W	1560 g
ECM18PT/ECM18PO	232 mm	392 mm	106 mm	-	382 mm	212 mm	68 mm	>25 W	2340 g
ECM24PT/ECM24PO	357 mm	283 mm	106 mm	125 mm	273 mm	336 mm	68 mm	>30 W	1560 g
ECM36PT/ECM36PO	482 mm	283 mm	106 mm	125 mm	273 mm	462 mm	68 mm	>30 W	1560 g
ECM48PT/ECM48PO	676 mm	283 mm	106 mm	125 mm	273 mm	656 mm	68 mm	>30 W	1560 g
ECM2x18PT/ECM2x18PO	357 mm	392 mm	106 mm	125 mm	382 mm	336 mm	68 mm	>30 W	2340 g
ECM3x18PT/ECM3x18PO	522 mm	392 mm	106 mm	125 mm	382 mm	502 mm	68 mm	>35 W	2340 g

