*CH14x51 aM 40A/500V

Fuse link

ETI Code:	**002631017**
Product group:	**C low Voltage cylindrical fuses**
Catalogue Group:	**C low Voltage cylindrical fuses**
Type description:	**CH**
Fuse type:	**CH**
Size:	**14x51**
Rated current:	**40 A**
Rated AC voltage:	**500 V**
Time-Current Characteristic:	**aM**
Breaking capacity AC:	**120 kA**
Application:	**For relays, contactors and motors protection in case of short-circuit**
Power dissipation:	**2.7 W**
Standards:	**IEC 60269-1, IEC 60269-2**

Online product page

Documents

TECHNICAL DATA CATALOG

INSTRUCTION MANUAL

CE DECLARATION

2D FILE

3D FILE

EPLAN FILE

ETIM

Size	**14x51 mm**
Breaking capacity	**120 kA**

Logistics

Product

EAN code for a single product	**3838895906629**
Net weight of the product	**18.75 g**
Net width	**14.3 mm**
Net height	**51 mm**
Net depth	**14.3 mm**
Stock unit of measure	**pcs**

Basic Packaging

Basic packaging quantity	**10 pcs**
EAN code for a basic packaging	**3838895169789**
Basic packaging weight	**0.186 kg**
Basic packaging volume	**0.126 dm³**

Transport Packaging

Transport packaging quantity	**500 pcs**
EAN code for a transport packaging	**3838895169796**
Transport packaging weight	**9.8 kg**
Transport packaging volume	**6.4 dm³**
Pallet quantity	**85,000 pcs**
Customs tariff	**85361050**

CutOff

Cut-off current characteristics CH14



Dimension



size	a	$b_{max.}$	c	$d_{min.}$	r
8 x 32	31,5±0,5	6,7	8,5±0,1	4	1±0,5
10 x 38	38,0±0,6	10,5	10,3±0,1	6	1,5±0,5
14 x 51	51,0+0,6/-1	13,8	14,3±0,1	7,5	±1
22 x 58	58,0+0,1/-2	16,2	22,2±0,1	11	±1

Energy characteristic

Melting energy characteristics I^2t CH14



I/t characteristic