



SL00 1P SP.95

Strip type fuse sw.disconnect.

ETI Code:	001692012
Type of Installation:	Busbar mounting
Size:	NH00
Rated current:	160 A
Number of poles:	3
Rated AC voltage:	690 V
Utilization category:	AC-23B
IP rating:	IP30

Online product page [🔗](#)

Documents



TECHNICAL DATA CATALOG



INSTRUCTION MANUAL



CE DECLARATION



2D FILE



3D FILE



EPLAN FILE

ETIM

Max. rated operation voltage Ue AC	690 V
Rated permanent current Iu	160 A
Suitable for fuses	NH000, NH00
Type of control element	Other
Conditioned rated short-circuit current Iq	120 kA
Cable entry	Other
Type of electrical connection of main circuit	Frame clamp
Degree of protection (IP), front side	IP30
Number of poles	3
Rated operation power at AC-23, 400 V	110 kW
Suitable for busbar mounting	Yes
Position control element	Front side

Logistics

Product

Net weight of the product	2.45 kg
Net width	49.6 mm
Net height	662.6 mm
Net depth	150.73 mm
Stock unit of measure	pcs

Transport Packaging

Transport packaging quantity	1 pcs
EAN code for a transport packaging	4029155537571
Transport packaging weight	2.053 kg
Transport Packaging Dimensions Height	165 mm
Transport Packaging Dimensions Width	663 mm
Transport Packaging Dimensions Depth	55 mm
Transport packaging volume	6.017 dm³
Pallet quantity	126 pcs
Customs tariff	85389099

