

SL3 3P SP.300

Strip type fuse sw.disconn.



ETI Code:	001692331
Type of Installation:	Busbar mounting
Size:	NH3
Rated current:	630 A
Number of poles:	3
Rated AC voltage:	690 V
Utilization category:	AC-23B
IP rating:	IP30

[Online product page](#) 

Documents



TECHNICAL DATA CATALOG



INSTRUCTION MANUAL



CE DECLARATION



2D FILE



3D FILE



EPLAN FILE

ETIM

Max. rated operation voltage Ue AC	690 V
Rated permanent current Iu	630 A
Suitable for fuses	NH1
Type of control element	Other
Conditioned rated short-circuit current Iq	120 kA
Cable entry	Other
Type of electrical connection of main circuit	Frame clamp
Degree of protection (IP), front side	IP30
Number of poles	3
Rated operation power at AC-23, 400 V	436 kW
Suitable for busbar mounting	Yes
Position control element	Front side

Logistics

Product

Net weight of the product	6.63 kg
Net width	100 mm
Net height	662 mm
Net depth	204.8 mm
Stock unit of measure	pcs

Transport Packaging

Transport packaging quantity	1 pcs
EAN code for a transport packaging	4029155875581
Transport packaging weight	6.202 kg
Transport Packaging Dimensions Height	205 mm
Transport Packaging Dimensions Width	764 mm
Transport Packaging Dimensions Depth	100 mm
Transport packaging volume	15.662 dm³
Pallet quantity	50 pcs
Customs tariff	85389099

